

We claim:

1. A method for establishing a label switched path by a first label switching device to a second label switching device in a communication network without using an explicit signaling protocol, the method comprising:

allocating a new label for the label switched path;  
generating a labeled packet including the new label; and  
forwarding the labeled packet to the second label switching device.

2. The method of claim 1, wherein generating the labeled packet comprises:  
inserting the new label into the packet; and  
setting an indicator in the packet to indicate that the packet is labeled.

3. The method of claim 2, wherein the indicator is an ethertype field of the packet, and wherein setting the indicator in the packet to indicate that the packet is labeled comprises setting the ethertype field to a predetermined value.

4. The method of claim 2, wherein the indicator is a bit in a header field of the packet, and wherein setting the indicator in the packet to indicate that the packet is labeled comprises setting the bit to a predetermined value.

5. The method of claim 1, further comprising:  
adding a forwarding table entry to a forwarding table, the forwarding table entry mapping the new label to a forwarding equivalence class and outgoing interface for the label switched path.

6. The method of claim 5, wherein the forwarding table is associated with the outgoing interface for the label switched path.

7. The method of claim 1, further comprising:

Sub  
AI  
cont

0087205 EST 06

20

25

30

terminating use of the label switched path; and  
forwarding unlabeled packets to the second label switching device.

AI  
5 Cont

8. The method of claim 7, further comprising:  
removing a forwarding table entry from a forwarding table, the forwarding table entry mapping the new label to a forwarding equivalence class and outgoing interface for the label switched path.

008720 0E58T960

9. A label switching device comprising:  
an outgoing interface providing an interface for communicating with a second label switching device; and  
packet processing logic operably coupled to allocate a new label for a new label switched path to the second label switching device and to forward a labeled packet including the new label to the second label switching device over the outgoing interface without first explicitly establishing the new label switched path to the second label switching device using a signaling protocol.

10. The label switching device of claim 9, wherein the packet processing logic comprises:  
label switching logic operably coupled to decide to establish the new label switched path;  
label allocation logic operably coupled to allocate the new label for the new label switched path; and  
packet labeling logic operably coupled to insert the new label in the packet and set an indicator in the packet to indicate that the packet is labeled.

11. The label switching device of claim 10, wherein the indicator is an ethertype field of the packet, and wherein the packet labeling logic is operably coupled to set the ethertype field to a predetermined value to indicate that the packet is labeled.

12. The label switching device of claim 10, wherein the indicator is a bit in a header field of the packet, and wherein the packet labeling logic is operably coupled to set the bit to a predetermined value to indicate that the packet is labeled.

13. The label switching device of claim 9, further comprising a forwarding table associated with the outgoing interface.

Sub  
5  
CP  
cont

00872050E5BT960

20

25

14. The label switching device of claim 13, wherein the packet processing logic further comprises label switched path setup logic operably coupled to add a forwarding table entry to the forwarding table, the forwarding table entry mapping the new label to a forwarding equivalence class and the outgoing interface for the label switched path.

5

15. The label switching device of claim 9, wherein the packet processing logic is operably coupled to forward unlabeled packets to the second label switching device over the outgoing interface upon deciding to stop using the label switched path.

16. The label switching device of claim 15, wherein the packet processing logic is operably coupled to remove a forwarding table entry from a forwarding table associated with the outgoing interface, the forwarding table entry mapping the new label to a forwarding equivalence class and the outgoing interface for the label switched path.

009720 "0658796

5  
Cont  
P1

17. A program product for use in a first label switching device, the program product comprising packet processing logic operably coupled to allocate a new label for a new label switched path to a second label switching device and to forward a labeled packet including the new label to the second label switching device over an outgoing interface without first explicitly establishing the new label switched path to the second label switching device using a signaling protocol.

18. The program product label switching device of claim 19, wherein the packet processing logic comprises:

label switching logic programmed to decide to establish the new label switched path;

label allocation logic programmed to allocate the new label for the new label switched path; and

packet labeling logic programmed to insert the new label in the packet and set an indicator in the packet to indicate that the packet is labeled.

19. The program product of claim 18, wherein the indicator is an ethertype field of the packet, and wherein the packet labeling logic is programmed to set the ethertype field to a predetermined value to indicate that the packet is labeled.

20. The program product of claim 18, wherein the indicator is a bit in a header field of the packet, and wherein the packet labeling logic is programmed to set the bit to a predetermined value to indicate that the packet is labeled.

21. The program product of claim 17, wherein the packet processing logic further comprises label switched path setup logic programmed to add a forwarding table entry to a forwarding table, the forwarding table entry mapping the new label to a forwarding equivalence class and the outgoing interface for the label switched path.

0018530071800  
008720706587960  
20

22. The program product of claim 17, wherein the packet processing logic is programmed to forward unlabeled packets to the second label switching device over the outgoing interface upon deciding to stop using the label switched path.

5 23. The program product of claim 22, wherein the packet processing logic is operably coupled to remove a forwarding table entry from a forwarding table associated with the outgoing interface, the forwarding table entry mapping the new label to a forwarding equivalence class and the outgoing interface for the label switched path.

008720" 0E58T960







34. The label switching device of claim 32, wherein the indicator is a bit in a header field of the packet, and wherein the bit is set to a predetermined value to indicate that the packet is labeled.

5 35. The label switching device of claim 31, wherein the label switched path setup logic is operably coupled to determine a forwarding equivalence class and outgoing interface for the packet based upon network layer addressing information in the packet and add a forwarding table entry to a forwarding table, the forwarding table entry mapping the new label to the forwarding equivalence class and outgoing interface for the packet.

36. The label switching device of claim 31, further comprising:  
routing logic responsive to the label switched path setup logic and operably coupled to forward the packet based upon the network layer addressing information in the packet.

008720" 0658796E

5 *Sub*  
*cat*  
*cat*  
37. A program product for use in a first label switching device, the program product comprising packet processing logic programmed to receive a labeled packet including a new label from the second label switching device over an incoming interface without first explicitly establishing the label switched path from the second label switching device to the first label switching device using a signaling protocol and to set up the label switched path using the new label.

38. The program product of claim 37, wherein the packet processing logic comprises: label detection logic programmed to determine that the received packet is labeled; label switching logic responsive to the label detection logic and programmed to determine that the labeled packet is not associated with an existing label switched path; and

label switched path setup logic responsive to the label switching logic and programmed to set up the label switched path using the new label.

20 *0081015*  
*0081015*  
39. The program product of claim 38, wherein the labeled packet includes the new label and an indicator indicating that the packet is labeled, and wherein the label detection logic is programmed to determine that the received packet is labeled based upon the indicator.

40. The program product of claim 39, wherein the indicator is an ethertype field of the packet, and wherein the ethertype field is set to a predetermined value to indicate that the packet is labeled.

25 41. The program product of claim 39, wherein the indicator is a bit in a header field of the packet, and wherein the bit is set to a predetermined value to indicate that the packet is labeled.

30 42. The program product of claim 38, wherein the label switched path setup logic is programmed to determine a forwarding equivalence class and outgoing interface for the

packet based upon network layer addressing information in the packet and to add a forwarding table entry to a forwarding table, the forwarding table entry mapping the new label to the forwarding equivalence class and outgoing interface for the packet.

- 5      43.      The program product of claim 38, further comprising:  
         routing logic responsive to the label switched path setup logic and programmed to forward the packet based upon the network layer addressing information in the packet.

008720" 0E58T960

44. A communication system comprising a first label switching device in communication with a second label switching device over a communication network, wherein the first label switching device and the second label switching device use a packet-driven mechanism to establish a label switched path from the first label switching device to the second label switching device without first explicitly establishing the label switched path using a signaling protocol.

45. The communication system of claim 44, wherein the first label switching device is operably coupled to allocate a new label for the label switched path and to forward a labeled packet including the new label to the second label switching device over the communication network upon deciding to establish a new label switched path to the second label switching device, and wherein the second label switching device is operably coupled to receive the labeled packet from the first label switching device and to set up the new label switched path using the new label from the labeled packet.

46. The communication system of claim 45, wherein the first label switching device is operably coupled to forward unlabeled packets to the second label switching device upon deciding to remove the label switched path, and wherein the second label switching device is operably coupled to remove the label switched path.

*Handwritten initials and signature:*  
SB  
CPL  
Cng

00918530 45

47. A communication message comprising a new label for a label switched path to be established and a label indicator indicating that the protocol message is labeled.

48. The communication message of claim 47, wherein the label indicator comprises an  
5 ethertype field having a predetermined value for indicating that the protocol message is labeled.

49. The communication message of claim 47, wherein the label indicator comprises a bit in a header field.

09518530 071800  
008740 08587960